



Lagerprogramm (Stock Programme)

Werkstoff-Nr. 2.4360 / Alloy 400 / UNS N 04400

✓ → vorrätig bei TK (in stock at TK)

□ → Werksvorrat oder aus Neufertigung (own production or in stock of producer)

Außendurchmesser (Outer Diameter) mm	Wandstärke (Wall Thickness) mm	Nennweite (Nom. Bore Inch)	Schedule (schedule)	Rohre (Pipes)	Bogen-1-90°-3 (Elbows LR 90°)	T-Stücke (Tees)	Bordscheiben DIN 2642 (Pressed Collars)
13,72	2,24	1/4"		✓			
— 17,20 —	— 2,30 —	— 3/8" —		— ✓ —	— ✓ —		
21,34	2,11	1/2"	10S	□	□		✓
21,34	2,77		40S	✓	✓	✓	✓
21,34	3,73		80s	□			
— 26,67 —	— 2,11 —	— 3/4" —	— 10S —	— □ —	— □ —		— ✓ —
— 26,67 —	— 2,87 —		— 40S —	— □ —	— ✓ —	— ✓ —	
— 26,67 —	— 3,91 —		— 80S —	— □ —			
33,40	2,60	1"	10S				✓
33,40	3,38		40S	✓	✓	✓	
33,40	4,55		80S	✓	✓		
— 42,16 —	— 2,77 —	— 1 1/4" —	— 10S —	— — —			
— 42,16 —	— 3,56 —		— 40S —	— — —	— ✓ —		
48,26	2,77	1 1/2"	10S	□	✓		✓
48,26	3,68		40S	✓	✓	✓	
— 60,30 —	— 2,77 —	— 2" —	— 10S —	— ✓ —	— □ —		— ✓ —
— 60,30 —	— 3,91 —		— 40S —	— ✓ —	— ✓ —	— ✓ —	
— 60,30 —	— 5,54 —		— 80S —	— □ —	— □ —		
76,10	2,50			—	✓		
76,10	2,90			—			
— 88,90 —	— 3,05 —	— 3" —	— 10S —	— ✓ —	— ✓ —	— ✓ —	— ✓ —
— 88,90 —	— 5,49 —		— 40S —	— ✓ —	— ✓ —	— ✓ —	
114,30	3,05	4"	10S	□	✓	✓	✓
114,30	6,02		40S	✓	✓	✓	
— 168,30 —	— 3,40 —	— 6" —	— 10S —	— ✓ —	— ✓ —		— ✓ —
— 168,30 —	— 7,11 —		— 40S —	— □ —	— □ —		
219,08	3,00	8"			□		
219,08	4,00				□		