



Lagerprogramm (Stock Programme)

Werkstoff-Nr. 2.4605 / Alloy 59 / UNS N 06459

✓ → vorrätig bei TK (in stock at TK)

□ → Werksvorrat oder aus Neufertigung (own production or in stock of producer)

Außendurchmesser (Outer Diameter) mm	Wandstärke (Wall Thickness) mm	w = geschweißt (welded) s = nahtlos (seamless)	Rohre (Pipes)	Bogen-1-90°-3 (Elbows LR 90°)	T-Stücke (Tees)	Bordscheiben DIN 2642 (Pressed Collars)
13,50	1,60	w		✓		□
— 17,20 —	— 1,60 —	— w —		— ✓ —		— □ —
21,30	2,00	w		✓		□
— 26,67 —	— 2,87 —	— s —	— ✓ —			— □ —
26,90	2,30	w		✓	✓	□
— 33,40 —	— 2,77 —	— w —	— ✓ —	— ✓ —	— ✓ —	— □ —
— 33,40 —	— 3,38 —	— s —	— □ —	— ✓ —	— ✓ —	— □ —
33,70	2,60	w		✓	✓	□
33,70	2,77	s				□
— 42,40 —	— 2,60 —	— w —			— ✓ —	— □ —
48,30	3,60	w				□
48,30	3,68	s	✓		✓	□
— 60,30 —	— 2,77 —	— w —	— ✓ —	— ✓ —	— ✓ —	— □ —
— 60,30 —	— 2,90 —	— w —				— □ —
— 60,30 —	— 3,91 —	— s —	— □ —	— ✓ —		— □ —
76,10	2,90	w	□	✓	✓	□
76,10	4,00	w	□	✓		□
— 88,90 —	— 3,05 —	— w —	— □ —	— ✓ —	— ✓ —	— □ —
— 88,90 —	— 3,20 —	— w —	— ✓ —	— ✓ —		— □ —
— 88,90 —	— 5,49 —	— s —	— ✓ —			— □ —
114,30	3,20	w	✓	✓	✓	□

